STEAM for Creative Innovation:
Practice based approach for integrating wearable technology in fashion design


TECHNIQUE-Draw, Draft and Drap

01 FASHION ILLUSTRATION

FASHION ILLUSTRATION:

Full outfit drawn on a figure with full styling.

These can be drawn with the use of a figure template. Conventional sketches are based on the ideal and standard body shape.






UGLY DRAWING AND ILLUSTRATION

Not requiring perfect drawing skill. Illustration is about the creative idea and design concept.

LET'S LOOK AT SOME ILLUSTRATIONS from FAMOUS FASHION BRANDS!!!



PRADA 2016SS



UGLY DRAWING AND ILLUSTRATION

YOHJI YAMAMOTO 2013FW





UGLY DRAWING AND ILLUSTRATION

MEADHAM KIRCHHOFF 2013FW

1EADHAM

KircHHOFF





UGLY DRAWING AND ILLUSTRATION

BALMAIN 2013SS









Balmain 2013SS Fashion illustrations by Rei Nadal

PRODUCTION DRAWING/ FLAT DRAWING

Production drawing shows the factory or pattern cutter the shape of the garment when laid flat, without any artistic flare or stylization.

It clearly shows the details of the garment, Including:

- Type of stitches
- Shape/detail e.g. darts or tucks
- Trims and fastenings





: J E N N Y K T R A N: FALL15-COLLECTION LOOK-3



TECHNIQUEOPEN SEAM AND DIY FASHION

HOW TO CREATE AN OPEN SEAM?

FIRST YOU NEED TO KNOW....

In order to create a seam you would need to sew through two or more pieces of fabric to connect them.

01 You will have two fabric or more

02 And you need to distinguish the right side and wrong side of the fabric

RIGHT SIDE: is the side that should be seen when you are wearing

WRONG SIDE: is the side that won't been seen when you are wearing





STEP 1

★ PUT ONE FABRIC UNDER THE OTHER FABRIC



NOTICE: The right side should be faced to each other

That's mean the wrong side should on top

102 HOW TO CREATE AN OPEN SEAM?

STEP 2

LEAVE A SEAM ALLOWANCE

A seam allowance is the space between a seam and the edge of the fabric.

How much is seam allowance? (UK / EU based) that is 1cm

STEP 3

★ SEW THE SEAM


You can sew the seam by hand stitching or using a sewing machine. And your seams can be straight or curved.

Then you can stitch the straight or curved line (RED LINE) to attach both fabric

Remember need to do backstitching at the beginning and the end of the stitching

(Wide) Straight

Seam Allowance 1cm



You can see the result after attaching two fabrics

And the next step : **OPEN THE SEAM**





13 HOW TO CREATE AN OPEN SEAM?

After sewing the seam:

1. Plain seam: a seam that has been stitched and pushed to one side.

2. Open seam: a seam that has been stitched and then pressed open.

Finally, you can overlock the edges of the seam allowance to create a clean edge














4

Basic Methods of clothes making

- 1. Draping
- 2. Drafting









- 1) Mark 1cm allowance
- 2) Right side to right side
- Follow the marked line to sew
- 4) Backstitches (in the beginning and end)
- 5) Open seam (Iron out)
- 6) Serger or overlock the edges

Draping

- 1. How to Pin
- 2. Type of fabric: Woven and Knit











Raquel Allegra

Vera Wang


6

Woven

- 1:1 Plain weave

- 1:2 Tweed weave

- 16:1 Satin weave









Clothbase




Hellessy

Givenchy, Stella McCartney, REFINERY29'S, VICTORIA BECKHAM

Knit

- Fine
- Chunk knit



Detail:

Cable, Jacquard

Style:

Cardigan/jumper/tee

Method:

Fully fashion, cut and sewn



JOURNAL STANDARD

Michael Kors

Prada, Celine, Chanel

Isabel Marant







Ralph Lauren


8

Basic Methods of clothes making Drafting





My Golden Thimble































UNDERCOVER

Bibhu Mohapatra

Louis Vuitton

Lana Mueller

9

Basic Methods of clothes making **Drafting**

Try different shapes and calculate





